

PK110S

Compact 4,100 lm Short Throw 4K UHD Laser Business Projector



The Optoma PK110S short throw projector delivers 4,100 lumens of brilliant 4K UHD sharp visuals in a compact short-throw design, enabling large, shadow-free projections even in limited spaces. Engineered for 24/7 reliability, it offers a low-maintenance, energy-efficient laser solution with centralized IT management and smart control for corporate, education, or commercial uses.

4,100 lumens brightness – Clear projection for spaces with ambient light

- 30,000h laser life – DuraCore laser ensures long-term reliability and low TCO
- Sustainable design – 50% recycled metal and PCR materials
- Optoma Management Suite (OMS) – Enables centralized IT monitoring and control across multiple networked devices
- Optoma Smart Control App – Intelligent screen alignment and remote control directly from your mobile device



Specification

Display

Technology	DLP®
Resolution	4K UHD (3840x2160)
Brightness	4,100 Lumens
Contrast ratio	2,300,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3, 16:9, 16:10, Full, Auto, Native
Keystone correction - horizontal	+/-15°
Keystone correction - vertical	+/-15°
Horizontal scan rate	15~150 KHz
Vertical scan rate	24~120 Hz
Uniformity	75%
Screen size	30"~300"



Light source

Light source type	Laser
Light source life	30,000 hours (Eco mode)

Optical

Throw ratio	0.496
Projection distance	Up to 3.294 M
Zoom	n/a
Zoom type	Fixed
Focal length	7.51mm
Native offset	114% (+/-5%)
Lens shift	n/a

Connectivity

Connections- Inputs	HDMI 2.0 x 2
Connections - Outputs	Audio Out x 1, USB-A (5V/1.5A) x 1, USB-A(5V/0.5A) x 1, 3D sync out x 1
Connections - Control	RJ45 x 1, RS232 x 1, 12V Trigger x 1

Specification

General

Noise level (min)	29 dB(A)
Noise level (max)	31dB (Bright mode)
PC compatibility	VGA,SVGA,XGA,720p,WXGA,SXGA,SXGA+,UXGA,1080p,WUXGA
2D compatibility	NTSC,PAL,SECAM,SDTV,HDTV,UHD
3D compatibility	Supports all HDMI 1.4a mandatory 3D formats (Frame pack, side-by-side, top-bottom) and up converts frame rate from 60Hz to 120Hz or 24Hz to 144Hz
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	27 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Simplified Chinese, Spanish, Swedish, Thai, Traditional Chinese, Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	Max Temperature(operating): 0 ~ 40°C; Tolerance +/- 2°C, Max Altitude(operating): 10,000 ft., for 0°C~30°C, Max humidity(operating): 80% RH, non-condensing
Remote control	Business remote control
Speaker count & Watts per speaker	1 x 15W
In the box	AC power cord Remote control Quick start user manual

Networking

LAN control	Yes
24/7 operation	Yes
360° operation	Yes

Power

Power supply	AC 100 ~ 240 V, 50 ~ 60 Hz
Power consumption (standby)	≤0.5 W
Power consumption (eco mode)	125 W@110VAC 124 W@220VAC
Power consumption (bright mode)	178 W @110VAC 176 W @220VAC

Specification

Weight and dimensions

Dimensions (W x D x H)	W/o feet: 216 x 274 x 108.5mm (10.8 x 8.5 x 4.3 inches) With feet: 216 x 274 x 114mm (10.8 x 8.5 x 4.5 inches)
Gross weight	4.61 ± 0.2KG
Net weight	3.1 ± 0.2KG

Applicable software

Optoma Management Suite	Yes
Optoma Smart Control App	Yes