

ZW521

Compact 6,000lm WXGA Laser Business Projector



The Optoma ZW521 is a 6,000lumen WXGA laser projector engineered for 24/7 reliability in business or education spaces. This compact, maintenance-free laser solution features a 30,000-hour lifespan, 1.3x optical zoom, smart control, and centralized IT management via Optoma Management Suite (OMS™) to support sustainable, energy-efficiency operation in business applications.

6,000lumen brightness – Clear projection for spaces with ambient light

- 30,000h laser life – DuraCore laser ensures long-term reliability and low TCO
- 1.3x zoom & geometric correction for flexible installation
- Sustainable design – 50% recycled metal and PCR materials for sustainability
- Optoma Management Suite (OMS™) – Enables centralized monitoring and control across multiple devices



Specification

Display

Technology	DLP®
Resolution	WXGA (1280x800)
Brightness	6,000l Lumens
Contrast ratio	300,000:1
Contrast ratio (Dynamic)	2,000,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Horizontal scan rate	15~102 KHz
Vertical scan rate	24~120 Hz
Uniformity	75%
Screen size	30"~300"



Light source

Light source type	Laser
Light source life	30,000 hours (Eco mode)

Optical

Throw ratio	1.18:1 ~ 1.54:1
Projection distance	1m~ 10m (mechanism travel) 1m to 5m (Optical travel)
Zoom	1.3
Zoom type	Manual
Focal length	16.90mm~21.60mm
Native offset	112% +/-5%

Connectivity

Connections- Inputs	HDMI 1.4 x2, VGA In x1, Audio 3.5mm x1
Connections - Outputs	USB-A 2.0 x2, 3D sync out x1, Audio 3.5mm x1
Connections - Control	RJ45 x1, RS232 x1, 12V trigger x1

Specification

General

Noise level (min)	29 dB(A)
Noise level (max)	29 dB(A)
PC compatibility	VGA,SVGA,XGA,720p,WXGA,SXGA,SXGA+,UXGA,1080p,WUXGA
2D compatibility	NTSC,PAL,SECAM,SDTV,HDTV,UHD
3D compatibility	Supports all HDMI 1.4a mandatory 3D formats (Frame pack, side-by-side, top-bottom) and up converts frame rate from 60Hz to 120Hz or 24Hz to 144Hz
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	27 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Simplified Chinese, Spanish, Swedish, Thai, Traditional Chinese, Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	Max Temperature(operating): 0 ~ 40°C; Tolerance +/- 2°C, Max Altitude(operating): 10,000 ft., for 0°C~30°C, Max humidity(operating): 80% RH, non-condensing
Remote control	Business remote control
Speaker count & Watts per speaker	1 x 15W
Input lag	4K/ 60Hz: 16.7 ms 1080P/ 60Hz: 16.7 ms 1080P/ 120Hz: 8.4 ms
In the box	AC power cord Remote control Quick start user manual

Networking

LAN control	Yes
24/7 operation	Yes
360° operation	Yes

Power

Power supply	AC 100 ~ 240 V, 50 ~ 60 Hz
Power consumption (standby)	≤0.5 W
Power consumption (eco mode)	150 W@110VAC 147 W@220VAC
Power consumption (bright mode)	210 W @110VAC 205 W @220VAC

Specification

Weight and dimensions

Dimensions (W x D x H)	W/o feet: 216 x 274 x 108.5mm (10.8 x 8.5 x 4.3 inches) With feet: 216 x 274 x 114mm (10.8 x 8.5 x 4.5 inches)
Gross weight	4.3 kg / 9.5 lbs
Net weight	2.9 Kg / 6.4 lbs