AZU617TSTN

High brightness short throw laser projector





Introducing the AZU617TSTN.

At 6,600 lumens, with 4K and HDR compatability, the AZU617TSTN features a dust resistant IP6X certified optical engine for 24/7 operational capabilities and low maintenance. The AZU617TSTN short throw projector features an extremely long-life laser technology, manual horizontal & vertical lens shift and built-in 15W speakers.

Suitable for a wide variety of applications, this projector is perfect for anywhere that requires a clean bright image including large venues, classrooms/lecture theatre's, museums, houses of worship, digital signage or immersive installations.

The added control flexibility of HDBaseT 3.0 and LAN make this projctor an affordable set and forget solution.

Copyright © Optoma 2025, Optoma and its logo is a registered trademark of Optoma Corporation and its affiliates (“Optoma”). All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners other than Optoma, and Optoma disclaims any and all rights in these marks. All specifications are subject to change without notice. All images are for representation purposes only and may be simulated or AI generated content.

Specification

Display/image

Display technology	DLP
Resolution	WUXGA (1920x1200)
Brightness	6,600 lumens
Contrast ratio	3,00,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+-15°
Keystone correction - vertical	+-15°
Displayable colours (millions)	1073.4
Horizontal scan rate	5~140HzKhz
Vertical scan rate	24~120HzHz
Uniformity	85%
Projection Size	30" ~ 300"

Lamp info

Light source type	Laser
Lamp watts	125
LASER life	30,000 hours

Optical

Throw ratio	0.58:1
Projection distance	0.38m - 3.75m
Zoom type	Fixed
Focal length	8.51
Lens shift	Vertical 100 ~ 110%, Horizontal: +/-4%
Native offset	110%
Lens shift	Yes - see product downloads for more information

Connectivity

Connections	Input Interface HDMI 2.0 input x 2 ; VGA input x 2 ; Audio input x 2 ; HDBaseT x 1 ; Video x 1 Output interface HDMI output x 1 ; 3D sync output x 1 ; Audio output x 1 ; USB Type A(Power 5V/1.5A) x 1 Control Interface RS-232 control x 1 ; RJ-45 network x 1 ; 12V Trigger x 1
LAN - wireless networking	No

Copyright © Optoma 2025, Optoma and its logo is a registered trademark of Optoma Corporation and its affiliates (“Optoma”). All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners other than Optoma, and Optoma disclaims any and all rights in these marks. All specifications are subject to change without notice. All images are for representation purposes only and may be simulated or AI generated content.

Specification

General

Noise level (min)	29dB
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
360° operation	Yes
Remote control	Backlit ProAV remote
Speaker count	2
Watts per speaker	15W
In the box	AC power cordRemote controlBasic user manual

Networking

LAN - control	Yes
LAN - wireless networking	No
LAN	Yes

Power

Power supply	Universal AC 100--240V± 10%~ 50 / 60 Hz with PFC input
Power consumption (standby)	
Power consumption (Eco mode)	216@110V ; 205W@220V
Power consumption (Bright mode)	366@110V ; 300W@220V

Weight and dimensions

Dimensions (W x D x H)	374 x 302 x 117
Gross weight	8.6 kg
Net weight	6.3 kg

Copyright © Optoma 2025, Optoma and its logo is a registered trademark of Optoma Corporation and its affiliates (“Optoma”). All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners other than Optoma, and Optoma disclaims any and all rights in these marks. All specifications are subject to change without notice. All images are for representation purposes only and may be simulated or AI generated content.