

X400LVeN

Bright projection



Project bright vibrant presentations effortlessly any time of day. Designed for meeting rooms and classrooms, the X400LVeN boasts amazing colour, long lamp life and energy-saving features for a lower overall cost of ownership.



This projector is easy to connect to with multiple inputs, a built-in speaker and USB Power. Perfect for connecting desktop or a laptop, for clear projected images with sound. This portable and lightweight projector can be installed or taken on the move for off-site meetings.

Specification



Display/image

Display technology	DLP™
Resolution	XGA (1024x768)
Brightness	4,000 lumens
Contrast ratio	25,000:1
Native aspect ratio	4:3
Aspect ratio - compatible	16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85Hz
Uniformity	75%
Screen size	0.71m ~ 7.73m (27.78" ~ 304.4") diagonal

Lamp info

Light source type	Lamp
Lamp watts	203
Lamp life hours (up to)	6000 (Bright), 12000 (Dynamic), 10000 (Eco)
LED+ life	15,000 hours

Optical

Throw ratio	1.94:1 ~ 2.16:1
Projection distance	1m - 12m
Zoom	1.1
Zoom type	Manual
Focal length	21.85 mm~24mm
Native offset	115%

Connectivity

Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA, 1 x Composite video, 1 x Audio 3.5mmOutputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1AControl 1 x RS232
-------------	---

General

Noise level (min)	27dB
Noise level (max)	29dB
PC compatibility	WUXGA, 1080p, UXGA, SXGA+, SXGA, WXGA+, WXGA, 720P, XGA, SVGA, VGA NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM
2D compatibility	B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
OSD / display languages	
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Speaker count	1
Watts per speaker	10W
In the box	AC power cordRemote controlBasic user manual

Specification

Power

Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	198W
Power consumption (max)	266W

Weight and dimensions

Dimensions (W x D x H)	316x243.5x108.5mm(w/ feet)
Gross weight	3.58 kg
Net weight	3 kg