

AZU517ST

High brightness short throw laser projector



Introducing the AZU517ST.

At 5,500 lumens, with 4K and HDR compatibility, the AZU517ST features a dust resistant IP6X certified optical engine for 24/7 operational capabilities and low maintenance. The AZU517ST short throw projector features an extremely long-life laser technology, manual horizontal & vertical lens shift and built-in 15W x 2 speakers.



Suitable for a wide variety of applications, this projector is perfect for anywhere that requires a clean bright image including large venues, classrooms/lecture theatre's, museums, houses of worship, digital signage or immersive installations.

Elevate your indoor golf experience with the AZU517ST projector's dedicated Golf Sim. mode. The Golf Sim. mode reproduces vivid green and blue of golf courses. From the texture of the grass to the layout of bunkers and water hazards, every element is displayed with crystal-clear clarity, enhancing your strategic planning and overall gaming experience.

The added control flexibility of LAN make this projector an affordable set and forget solution.

Specification



Display/image

Display technology	DLP
Resolution	WUXGA (1920x1200)
Brightness	5,500 lumens
Contrast ratio	3,00,000:1
Contrast ratio - dynamic	30,00,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-15°
Keystone correction - vertical	+/-15°
Has vertical auto keystone correction	Yes
Displayable colours (millions)	1073.4
Horizontal scan rate	15~140Khz
Vertical scan rate	24~120Hz
Screen size	0.76m ~ 7.62m (30" ~ 300") diagonal

Lamp info

Light source type	Laser
LASER life	30,000 hours

Optical

Throw ratio	0.58:1
Projection distance	0.38m - 3.75m
Zoom type	Fixed
Focal length	8.51
Lens shift	Vertical -100 ~ 110%, Horizontal --4 ~ 4%
Native offset	110%
Lens shift	Yes - see product downloads for more information
F/	2.75

Connectivity

	Input Interface : HDMI 2.0 ×2, VGA ×1, Composite video ×1, Audio 3.5mm ×2,
Connections	Output Interface : USB-A power(5V/1.5A) ×1, Audio 3.5mm ×1, 12V trigger ×1,VGA Out x1
	Control Interface : RS232 ×1, RJ45 ×1
LAN - wireless networking	No

Specification

General

Noise level (min)	29dB
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
360° operation	Yes
Remote control	Backlit ProAV remote
Speaker count	2
Watts per speaker	15W
In the box	AC power cordRemote controlBasic user manual

Networking

LAN - control	Yes
LAN - wireless networking	No
LAN	Yes

Power

Power supply	Universal AC 100--240V± 10%~ 50 / 60 Hz
Power consumption (standby)	
Power consumption (min)	300W ±15%@ 110V ; 295W ±15% @ 220V
Power consumption (max)	366W ±15%@ 110V ; 355W ±15% @ 220V

Weight and dimensions

Dimensions (W x D x H)	374 x 302 x 117
Gross weight	8.3±0.5 kg
Net weight	6.3±0.5 kg