

LH351

Optoma LH351 Full HD 3500 Lumens Business and Education Projector



Optoma LH351 is a versatile Full HD projector with 3500 lumens of brightness, designed for business, education, and entertainment environments. With a long-lasting, lamp-free 4LED light source, it delivers bright, vivid visuals and reliable performance in meeting rooms, classrooms, and a wide range of business and entertainment settings—including DIY golf simulation setups.

3500 lumens for clear visuals in ambient lighting conditions

- Centralized control with Optoma Management Suite Cloud (OMSC)
- Up to 30,000 hours lifespan for long-lasting performance
- Eco-conscious design for energy-efficient operation



Specification

Display

Technology	DLP®
Resolution	FHD (1920x1080)
Brightness	3,500 Lumens
Contrast ratio	300,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:10, Full, Native, Auto
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Horizontal scan rate	15~135 KHz
Vertical scan rate	24~120Hz
Uniformity	85%
Screen size	30" ~ 300"



Light source

Light source type	4LED
Light source life	30,000 hours (Eco mode)

Optical

Throw ratio	1.49 ~ 1.64
Projection distance	1.96 m ~ 4.89 m
Zoom	1.1x
Zoom type	Manual
Focal length	22 mm ~ 24.1 mm
Native offset	102.5% ±3%
Lens shift	n/a

Connectivity

Connections- Inputs	HDMI 2.0 x2, VGA x1, Audio in x1
Connections - Outputs	USB-A power 2A x1, Audio 3.5 mm x1, VGA x1
Connections - Control	RS232 x1, 1LAN x1

Specification

General

Noise level (min)	29 dB(A)
Noise level (max)	35 dB(A)
PC compatibility	VGA,SVGA,XGA,720p,WXGA,SXGA,SXGA+,UXGA,1080p,WUXGA
2D	NTSC,PAL,SECAM,SDTV,HDTV,UHD
3D compatibility	Auto, SBS, Top and Bottom, Frame Sequential, Frame Packing
Security	Kensington Lock, Password protected interface
OSD / display languages	27 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Simplified Chinese, Spanish, Swedish, Thai, Traditional Chinese, Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	Max Temperature(operating):0 ~ 40°C; Tolerance +/- 2°C, Max Altitude(operating): 10,000 ft., for 0°C~30°C, Max humidity(operating): 80% RH, non-condensing
Remote control	Backlit remote control
Speaker count & Watts per speaker	1 x 10W
Input lag	33.7ms (4K/60Hz) 16.7ms (1080P/60Hz) 8.4ms (1080P/120Hz)
In the box	Power cord Remote control 2 x AAA batteries (varies by region) Quick start user manual

Networking

LAN control	Yes
-------------	-----

Power

Power supply	AC 100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	≤0.5 W
Power consumption (eco mode)	130W @100VAC 124W @240VAC
Power consumption (bright mode)	226W @100VAC 212W @240VAC

Specification

Weight and dimensions

Dimensions (W x D x H)	W/o feet: 307 x 228 x 114.4 mm (12.09 x 8.98 x 4.50 inches) With feet: 307 x 228 x 125.4 mm (12.09 x 8.98 x 4.94 inches)
Gross weight	4.9 kg (+/- 10%) / 10.8 lbs
Net weight	3.1 kg (+/- 10%) / 6.8 lbs

Applicable software

Optoma Management Suite Cloud	Yes
-------------------------------	-----