

ZU2200

Ultra bright professional WUXGA laser projector



The high brightness ZU2200 professional laser projector fills a need for high-end installations, including the entertainment, exhibition, and digital signage markets. Part of Optoma's Ultra Bright Series, this projector offers incredibly high brightness of 22,000 lumens as well as extreme flexibility with eight interchangeable lenses to meet the needs of even the most complex installations.



As part of the Optoma DuraCore laser line up, the Ultra Bright Series high-performance projectors feature 4K HDR compatibility, pure engine video processing and colour matching to produce visually striking, lifelike images with exceptional detail and high colour accuracy. Additionally, the ZU2200 achieves superior colour rendition through MultiColor Laser (MCL) technology.

Strong reliability is at the core of the Ultra Bright Series projectors, with 24/7 operation capabilities, up to 30,000 hours of laser lifetime, and an IP5X rating for optimal and dependable performance, even under more extreme conditions up to 122 degrees Fahrenheit / 50 degrees Celsius. With a robust metal chassis and modular design for easier maintenance, a multitude of connectivity options, and failsafe redundancy mode for instant source switching, the Ultra Bright Series projectors offer a solution for intricate installations, including multi-projector and dome projection applications.

Specification



Display/image

Display technology	DLP
Resolution	WUXGA (1920x1200)
Brightness	22,000 lumens
Contrast ratio	2,000,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	16:9,16:10
Keystone correction - horizontal	+/-20°
Keystone correction - vertical	+/-20°
Screen size	Dependent on lens

Lamp info

Light source type	DuraCore MultiColor Laser
LASER life	30,000 hours

Optical

Throw ratio	Dependent on lens
Projection distance	Dependent on lens
	BX-CTA11, 0.65~0.75:1
	BX-CTA18, 0.84~1.02:1
	BX-CTA19, 1.02~1.36:1
Lens options	BX-CTA20, 1.2~1.5:1
	BX-CTA21, 1.5~2.0:1
	BX-CTA22, 2.0~4.0:1
	BX-CTA23, 4.0~7.2:1
	BX-CTA27, 7.2~10.8:1

Connectivity

Connections	Inputs 1 x RS232, 1 x 3D sync, 1 x Wired remote, 1 x HDBaseT, 1 x DisplayPort, 2 x HDMI, 1 x VGA, 1 x DVI-D, 1 x 3G-SDIOutputs 1 x RS232, 1 x 3D sync, 1 x Wired remote, 1 x HDMI, 1 x 3G-SDIControl 1 x RJ45, 1 x USB-A service, 1 x 12V trigger
LAN - wireless networking	No

General

Noise level (min)	38dB
Noise level (max)	40dB
3D	Full 3D
IP rating	IP5X
360° operation	Yes
Operating conditions	Operating: 10~85%RH, non-condensing. Storage: 5~90%RH, non-condensing
Remote control	Backlit ProAV remote

Specification

Networking

LAN - control	Yes
LAN - wireless networking	No
LAN	Yes

Power

Power supply	AC 100–240 V @ 50/60 Hz
Power consumption (standby)	0.5W
Power consumption (min)	590W
Power consumption (max)	1,900W

Weight and dimensions

Dimensions (W x D x H)	650 x 682 x 300.86
Gross weight	66.5 kg
Net weight	54 kg