

ZK608TST

High brightness short throw 4K UHD professional laser projector



****Spectacular 4K UHD image quality, low maintenance and ultimate reliability****

At 6000 lumens, with 4K and HDR compatibility, the ZK608TST combines a long-lifetime light source of up to 30,000 hours and an independent IP6X certified optical engine for 24/7 operation, offering truly maintenance-free projection. Added features include a short throw lens, manual horizontal and vertical lens shift and built-in 15W speakers.



Designed with the environment in mind, this projector features an eco-friendly chassis design made with up to 50% PCR (Post-Consumer Recycled) plastics and the packaging contains up to 97% recyclable materials.

Suitable for a wide variety of applications, this projector is perfect for anywhere that requires a bright and high quality image including large venues, classrooms, lecture theatres, museums, houses of worship, digital signage and immersive installations.

The added control flexibility of HDBaseT 3.0 for uncompressed audio and video content, RS232, LAN and OMS (Optoma Management Suite) Local makes this projector an affordable set-up and forget solution.

Specification

Display/image

Display technology	DLP
Resolution	UHD (3840x2160)
Brightness	6,000 lumens
Contrast ratio	3,00,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9
Keystone correction - horizontal	+/-15°
Keystone correction - vertical	+/-15°
Displayable colours (millions)	1073.4
Uniformity	85%
Screen size	0.76m ~ 7.62m (30" ~ 300") diagonal



Lamp info

Light source type	Laser
LASER life	30,000 hours

Optical

Throw ratio	0.58:1
Projection distance	0.38m - 3.75m
Zoom type	Fixed
Focal length	8.51
Lens shift	Vertical -106 ~ 116%, Horizontal: +/-4%
Native offset	106%
Lens shift	Yes - see product downloads for more information

Connectivity

Connections	Input Interface
	HDMI 2.0 input x 2 ; VGA input x 2 ; Audio input x 2 ; HDBaseT x 1
	Output interface
LAN - wireless networking	HDMI output x 1 ; 3D sync output x 1 ; Audio output x 1 ; USB Type A(Power 5V/1.5A) x 1
	Control Interface
	RS-232 control x 1 ; RJ-45 network x 1 ; 12V Trigger x 1
	No

Specification

General

Noise level (min)	33dB
Noise level (max)	36dB
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
360° operation	Yes
Remote control	Backlit ProAV remote
Speaker count	2
Watts per speaker	15W

Networking

LAN - control	Yes
LAN - wireless networking	No
LAN	Yes

Power

Power supply	AC input 100 ~ 240V, 50 / 60 Hz
Power consumption (standby)	
Power consumption (min)	300W
Power consumption (max)	366W

Weight and dimensions

Dimensions (W x D x H)	374 x 302 x 117
Gross weight	8.6 kg
Net weight	6.3 kg