

明亮且可靠的雷射專業投影機

- 投影機不僅更明亮、更耐用，同時也具有優異的色彩表現
- 與同等級之燈泡機型相比，有著更穩定的亮度輸出且更低的能耗表現
- 短焦鏡頭設計，可輕鬆投射 100 吋 大畫面。
- 待機模式與無汞燈設計可有效減輕碳排放，對未來環境也更加友善
- 獨家防塵光引擎設計更取得IP6X認證
- 支援24/7長效運轉之使用
- 支援一上電或接收訊源即自動開機
- 支援4K與HDR訊源
- 同時支援水平與垂直影像手動校正，最大化您的安裝使用彈性
- 支援垂直鏡頭位移
- 支援多種網路控制通訊協定
- **Optoma Management Suite (OMS)** 集中管理與控制所有裝置
- 支援 OTA (Over-the-Air) 韌體更新，輕鬆保持系統在最新狀態



Display/Image	Display technology	DLP™
	Resolution	4K UHD (3840x2160)
	Brightness	5,100 lumens
	Contrast ratio	300,000:1
	Native aspect ratio	16:9
	Aspect ratio - support	4:3, 16:9, 16:10, Full, Auto, Native
	Keystone correction	H±15°, V±15°
	Horizontal scan rate	15~150 KHz
	Vertical scan rate	24~120Hz
	Uniformity	75%
	Screen size	30"~300"
Light Source	Light source type	Laser
	Light source life	30,000 hours (Eco mode)
Optical	Throw ratio	0.79
	Projection distance	Up to 5.3M
	Zoom	n/a
	Zoom type	Fixed
	Focal length (mm)	11.6mm
	Lens shift	106%~127%
	Native offset	106%~127%(+/-5%)
Connectivity	Connections	Inputs HDMI 2.0 x 2, Audio In x 1, Outputs Audio Out x 1, USB-A (5V/1.5A) x 1, USB-A(5V/0.5A) x 1, 3D sync out x 1 Control RJ45 x 1 (LAN Control), RS232 x 1, 12V Trigger x 1
General	Noise level (min)	29dB (Eco mode)
	Noise level (max)	31dB (Bright mode)
	PC compatibility	VGA,SVGA,XGA,720p,WXGA,SXGA,UXGA,1080p,WUXGA
	2D compatibility	NTSC,PAL,SECAM,SDTV,HDTV,UHD
	3D compatibility	Supports all HDMI 1.4a mandatory 3D formats (Frame pack, side-by-side, top-bottom) and up converts frame rate from 60Hz to 120Hz or 24Hz to 144Hz
	3D	Full 3D
	Security	Kensington Lock, Password protected interface
	OSD / display languages	27 languages: English, Arabic, Czech, Danish, Dutch, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romania, Russian, Simplified Chinese, Spanish, Swedish, Thai, Traditional Chinese, Turkish, Vietnam
	Operating conditions	Max Temperature(operating):0 ~ 40°C; Tolerance +/- 2°C, Max Altitude(operating): 10,000 ft., for 0°C~30°C, Max humidity(operating): 80% RH, non-condensing
	24/7 operation	Yes
	Speaker count	1
	Watts per speaker	15W
	Input lag	4K/ 60Hz: 20 ms 1080P/ 60Hz: 20 ms 1080P/ 120Hz: 12.5 ms 1080P/ 240Hz: 6.5 ms
	In the box	AC power cord, Remote control, Basic user manual
Networking	LAN - control	Yes
Power	Power supply	100 ~ 240V, 50 ~ 60Hz
	Power consumption (standby)	≤0.5W
	Power consumption (Eco mode)	147 W@110VAC 146 W@220VAC
	Power consumption (Bright mode)	196 W @110VAC 193 W @220VAC
Weight and dimensions	Dimensions (W x D x H)	W/o feet: 216 x 274 x 108.5mm (10.8 x 8.5 x 4.3 inches) With feet: 216 x 274 x 114mm (10.8 x 8.5 x 4.5 inches)
	Gross weight	4.9±0.2KG
	Net weight	3.25±0.2KG