

CinemaX Pro

All-in-one entertainment system for professional installation



- **4K UHD HDR with high-performance glass lens**
- **3,500 lumens laser light source with 2,500,000:1 contrast ratio**
- **Dolby Digital 2.0 audio with 2 full range aluminum drivers and 2 woofers**
- **Smart+ technology with Alexa, Google Actions and IFTTT integration, and InfoWall**

Easily outfit home theaters with the cinematic, 4K UHD, 3,500 lumens, ultra short throw, Optoma CinemaX Pro. The space-saving design, high-performance glass lens and 81-point image warping adjustments ensures an easy huge screen experience that easily adapts to any installation environment.

Wide color gamut and HDR support with a 2,500,000:1 contrast ratio provides stunning color accuracy, brighter whites and deeper black levels. An integrated Dolby Digital 2.0 soundbar with two full range aluminum drivers, two woofers, ported, isolated chambers and 40 watts of power, engineered by NuForce, delivers crisp details with superior dialogue clarity.

Smart+ technology enable Amazon Alexa, Google Assistant and IFTTT support for easy integration into your smart home while InfoWall provides a personalized, configurable information display. An Android OS with smart TV apps and Optoma Marketplace deliver USB media playback compatibility, Internet streaming services and downloadable apps.

Specifications

Display/imagen	
Tecnología de visualización	DLP™
Resolución	UHD (3840x2160)
Brillo	3,500 lumens
Ratio de contraste	2,500,000:1
Relación de aspecto nativo	16:9
Ratio de aspecto - compatible	4:3
Frecuencia de muestreo horizontal	31 ~ 135Khz
Frecuencia de muestreo vertical	24 ~ 120Hz
Uniformidad	90%
Tamaño de pantalla	85" ~ 120" diagonal
Info Lámpara	
Fuente de luz	Laser
Vida del LÁSER	20,000horas
Óptica	
Distancia de tiro	0.25:1
Distancia de proyección (m)	18.5" - 25.98"
Distancia focal (mm)	525mm/20.669"
Offset nativo	124%
Conectividad	
Conexiones	Entradas 3 x HDMI 2.0, 1 x USB-A lector Salidas 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x USB-A servicio, 1 x RJ45
General	
Nivel sonoro (típico)	26dB
Nivel sonoro (max)	28dB
Compatibilidad PC	UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Compatibilidad 2D	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)
Compatibilidad 3D	Frame-pack: 1080p24, 720p50 / 60
3D	Full 3D
Seguridad	Kensington Lock, Interfaz protegida por contraseña
idiomas OSD / display	11 idiomas: Inglés, Francés, Alemán, Italiano, Japonés, Portugués, Ruso, Chino (simplificado), Español, Chino (tradicional)
Condiciones de funcionamiento	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Control remoto	Si
Altavoces	2
Watios por altavoz	10W
Contenido de la caja	AC power cord Rechargeable remote control Basic user manual
Input lag	70.00ms
Corriente	
Fuente de alimentación	100 ~ 240V, 50 ~ 60Hz
Consumo energético (standby)	0.5W
Consumo energético (mín.)	220W
Consumo energético (máx.)	345W
Peso y dimensiones	
Dimensiones (W x D x H)	22.68" x 15.08" x 5.12"
Gross weight	29.76 lbs
Net weight	24.25 lbs

