


ZU750

Spectacular image quality, low maintenance and ultimate reliability



© Circus Roncalli

- **30,000 hours maintenance-free laser light source**
- **Dust resistant – Independently tested, IP5X certified for total reliability**
- **8000 lumens laser WUXGA DLP projector**
- **Installation flexibility – 7x lens options including ultra short throw and dome lens**

The ZU750 builds on the success of the Duracore range of professional installation projectors. With enhanced features such as warping and edge blending, it joins the DuraCore laser line up which combines industry-leading lifetime of the light source with an independent dust resistant certification for ultimate peace of mind.



Specifications

Display/image	
Display technology	DLP™
Resolution	WUXGA (1920x1200)
Brightness	8,000 lumens
ANSI brightness	7,500
Contrast ratio	2,000,000:1
Contrast ratio - dynamic	6,000:1
Contrast ratio - full on/off	2,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-20°
Keystone correction - vertical	+/-20°
Uniformity	90%
Screen size	Dependent on lens
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	Dependent on lens
Projection distance	Dependent on lens
Lens options	BX-CTA16- 0.36 ~ 0.36 BX-CTA17- 0.65~0.75 BX-CTA15- 0.75 ~ 0.95 BX-CTA01- 0.95 ~ 1.22 BX-CTA06- 1.22 ~ 1.53 BX-CTA03- 1.52 ~ 2.92 BX-CTA13- 2.90 ~ 5.50 BX-CTADOME- Dome lens
Connectivity	
Connections	Inputs 2 x HDMI, 1 x DVI-D, 1 x VGA, 1 x HDBaseT, 1 x 3D sync Outputs 1 x VGA, 1 x 3D sync, 1 x USB-A Control 1 x RS232, 1 x Wired remote, 1 x mini USB service, 1 x RJ45
General	
Noise level (typical)	36dB
Noise level (max)	38dB
PC compatibility	HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
2D compatibility	PAL (625/576i/p), SECAM, NTSC (525/480i/p), HDTV (720p, 1080i/1080p)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock
IP rating	IP5X
OSD / display languages	11 languages: Dutch, English, French, German, Indonesian, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
24/7 operation	Yes
360° operation	Yes
Operating conditions	5°C~40°C/41°F~104°F
Remote control	Wired ProAV remote
Heat dissipation	2,109BTU/hour
In the box	Remote control, 2x AAA batteries, Power lead, VGA cable, Standard Lens ring (A01, A03, A13 ONLY) , A06 Lens ring
Optional wireless models	QuickCast Bundle, QuickCast starter kit
Networking	
LAN	Yes
Power	
Power supply	100 - 240V, 50 - 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	299W
Power consumption (max)	618W
Weight and dimensions	
Dimensions (W x D x H)	19.06" x 20.04" x 7.28"
Gross weight	48.94 lbs
Net weight	38.14 lbs

