

UHZ50

Smart 4K UHD laser home Cinema projector









- True 4K UHD resolution and laser technology HDR and HLG compatible
- Bright 3,000 lumens and stable output, achieves 2,500,000 : 1 Contrast.
- Superb Gaming Experience with 240Hz refresh rate and extremely low 4ms Input Lag for PC gaming
- PureMotion MEMC delivers judder free motion video

Entering the new generation of home entertainment with UHZ50. With DuraCore Laser technology, UHZ50 is able to deliver longer-lasting and excellent performance at true 4K UHD resolution with high brightness at 3,000 lumens and 2,500,000:1 contrast. UHZ50 also comes with the upgraded Smart Home features including Optoma Marketplace, File Manager, Creative Cast, and connectivity with voice assistants, offering the comprehensive home entertainment experience.

With the ability to implement 4-corner adjustment, 2D keystone correction, vertical lens shift, powered 1.3x zoom, and warping at 3*3 matrix, UHZ50 is also perfectly easy to install in any room at home, or to create a simulation scenario.

Specifications

Wireless - technology

Power

Power supply

Gross weight

Wireless - operating frequency

Power consumption (standby)

Power consumption (min)

Power consumption (max)

Weight and dimensions
Dimensions (W x D x H)

Display/image DIPTM Display technology Resolution UHD (3840x2160) Brightness 3,000 lumens Contrast ratio 2,500,000:1 16:9 Native aspect ratio 4:3.16:9.16:10 Aspect ratio - compatible Keystone correction -+/-30° horizontal Keystone correction - vertical +/-30° Has vertical auto keystone Yes correction Displayable colours (millions) 1073.4 Horizontal scan rate 31~135Khz Vertical scan rate 24 ~ 120HzHz Uniformity 80% 0.87m ~ 7.68m (34.1" ~ 302.4") diagonal Screen size Lamp info Light source type Lase LASER life 30,000 hours Optical 1.21:1 ~ 1.59:1 Throw ratio Projection distance 1.2m - 8.1m Zoom Zoom type Manual 12.81mm~16.74mm Focal length Lens shift Vertical +10% Native offset 105% Lens shift Yes - {{downloads_link}} Connectivity Connections Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC), 1 x Outputs 1 x Audio 3.5mm, 1 x S/PDIF Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync IEEE 802.11 b/g Wireless - technology Wireless - security WEP, TKIP, AES, WPA, WPA2 Wireless - operating frequency 2.4GHz General Noise level (typical) 26dB UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac PC compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz 2D compatibility SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) HDMI1/ HDMI2: Frame Packing(1280x720@50Hz/60Hz, 3D compatibility 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz) HDMI3: Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 1024x768@120Hz. 1280x800@120Hz. 1920x1080@120Hz) Top and Bottom(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz). 3D Full 3D Security bar, Kensington Lock, Password protected interface OSD / display languages 11 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 24/7 operation Operating conditions 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Remote control Backlit home remote 785BTU/hour Heat dissipation Speaker count 2 10W Watts per speaker In the box AC power cord Remote control Quick start user manual 4.00ms Input lag Networking

IEEE 802.11 b/g

100V ~ 240V, 50-60Hz

337 x 265 x 119.3 6.5 kg

2.4GHz

<0.5W

204W

276W







Net weight

4.8 kg

Copyright © 2022, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 08122022115307