

W335

Bright WXGA Projector



Features

- Luminous WXGA projection with 3,800 lumens and 22,000:1 contrast ratio
- HDMI, VGA and composite connectivity
- Up to 15,000-hour lamp life
- Vertical keystone for easy positioning
- Integrated 10-watt speaker



Robust I/O and superior performance

Enhance spaces with captivating 3,800 lumens WXGA images with the Optoma W335. Its 22,000:1 contrast ratio, 1.55 - 1.73:1 throw ratio and 1.1x zoom make it ideal for small-to-medium spaces, such as classrooms, offices and training spaces.

Vertical keystone support simplifies placement for easy installation. An integrated 10-watt speaker delivers crisp, room-filling audio that enhances presentations and videos without any additional equipment.

Robust input options, including HDMI, VGA and composite enable connectivity to a wide range of devices. A 15,000-hour lamp life enables many years of use with minimal maintenance.



W335



TECHNICAL SPECIFICATIONS

Aspect Ratio	16:10
Audio	10W speaker
Brightness	3,800 lumens
Compatible Aspect Ratio	16:10 (native), 16:9 and auto compatible
Connections	1 x HDMI v1.4a, 1 x VGA, 1 x composite, 1 x audio-in, 1 x USB-A (5v / 1.0 amp), 1 x VGA, 1 x audio, 1 x RS232
Contrast Ratio	22,000:1
Display Technology	Texas Instruments 0.65" WXGA DMD
Displayable Colors	1.07 billion
Keystone Correction	± 40° Vertical
Light Source Type	203W
Light Source Life	15,000/12,000/10,000/6,000 (Eco+/Dynamic/Eco/Bright)
Lens Shift	None
Maximum Resolution	WUXGA (1920 x 1200)
Native Resolution	WXGA (1280 x 800)
Noise Level	27dB
Offset	115% ± 5%
On-Screen Display	Complete on-screen menu adjustments in 26 languages
Operating Temperature	Sea Level to 10,000 feet (@73°F); must manually switch to high-altitude mode at 5,000 feet & above
Power Consumption	230W (Bright) / 190W (Eco)
Power Supply	AC input 100-240V, 50-60Hz, auto-switching

Projection Distance	3.9' - 45.9' (without zoom)
Projection Lens	F=2.41~2.53, F=21.85~24 mm
Projection Screen Size	29.7" - 300.7"
Remote Control	IR remote control
Throw Ratio	1.55 - 1.73:1

COMPATIBILITY SPECIFICATIONS

3D Compatibility	Side-by-Side: 1080i50 / 60, 720p50 / 60, Frame-pack: 1080p24, 720p50 / 60, Over-Under: 1080p24, 720p50 / 60
Computer Compatibility	WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA resized, VESA, PC and Mac
Horizontal Scan Rate	15.3 - 91.1kHz
RoHS	Compliant
Vertical Scan Rate	50-85 Hz (120Hz for 3D feature projector)
Video Compatibility	HDTV (720p, 1080i/p), SDTV (480i/p, 576i/p)

PHYSICAL SPECIFICATIONS

Dimensions (W x H x D)	12.4" x 3.9" x 9.6"
Security	Security bar, Kensington lock, password protection, keypad lock
Weight	6.7 lbs.

Other

What's in the Box?	W335, AC power cable, remote control, batteries, quick start user manual
Accessories	Carrying case: BK-4028, Lamp (replacement): BL-FU200D, QuickCast Pro 4K HDMI starter kit: QCP-4K-KIT (2 TX, 1 RX, 1 Cradle), QuickCast Pro 4K HDMI starter kit: QCP-SK-4K-HDMI (1 TX and 1 RX), Remote
Part Numbers	(replacement): BR-3079N, Universal ceiling mount: BM-5001U, Universal Ceiling mount: OCM815W, Universal Ceiling mount: OCM818W-RU
UPC	796435 44 249 1
Warranty Info	1-Year parts and labor limited warranty on the projector, 90 days lamp warranty

*Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

† 3D content can be viewed with DLP® Link active shutter glasses when projector is used with a compatible 3D player. Please visit Optoma.com for more information.

Optoma.com

Copyright © 2020 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change.
Published on 12/14/20