

ML750

Ultra-compact LED projector









- HD Ready and LED technology Great for movies, gaming and PC-free presentations
- Great connectivity HDMI, MHL, micoSD and built-in speaker
- Built in media play and optional wireless presentations
- Compact and lightweight <0.4kg



The ML750 ultra-compact portable LED projector is easily transportable between your home and office. This tiny projector weights less than 0.4kg and comes with a convenient carry bag. Watch HD movies, play video games or even present that winning presentation, the ML750 has everything you need to impress your audience.

Specifications

Gross weight

Net weight

Specifications	
Display/image	
Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness (HK/ANSI)	700/450
Contrast ratio	20,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	85%
Screen size	17" ~ 100" diagonal
Lamp info	Tr Too diagonal
Light source type	LED
LED life	20,000 hours
Optical	
Throw ratio	1.5:1
Projection distance	21.65" - 127.17"
Zoom type	Fixed
Focal length (mm)	14.95mm/0.589"
Native offset	100%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x microSD card,
	1 x USB-A reader
	Outputs 1 x Audio 3.5mm
General	
Noise level (typical)	30dB
Noise level (max)	32dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz)
3D compatibility	SVGA 120Hz, XGA 120Hz
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	12 languages: Dutch, English, French, German, Greek, Italian,
con , anopia, ianguages	Polish, Portuguese, Russian, Spanish, Swedish, Turkish
Operating conditions	5°C~35°C/41°F~95°F, max altitude 2500M/8202.5ft, max
	humidity 85%
Remote control	Card style
Speaker count	1
Watts per speaker	1W
In the box	Carry bag
	Universal I/O cable
	AC power cord Remote control
	Battery
	Basic user manual
Input lag	16.00ms
Optional wireless models	WUSB
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	16W
Power consumption (max)	26W
Weight and dimensions	
Dimensions (W x D x H)	4.13" × 4.17" × 1.54"
Gross weight	3.02 lbs

3.02 lbs

0.84 lbs





