


## HD39Darbee

Get closer! More depth, more detail



- **Amazing colour - accurate Rec.709 colours - 3500 ANSI lumens**
- **Award winning Darbee Visual Presence™ technology inside**
- **Installation flexibility – Vertical lens shift and 1.6x zoom**
- **Easy connectivity - 2x HDMI and MHL support and built-in 10W speaker**

The HD39Darbee couples high-end home cinema performance with bright, vibrant visuals to produce a stunning Full HD 1080p viewing experience. It also integrates DARBEE Visual Presence™ image enhancement technology to bring you revolutionary levels of depth and realism.



# Specifications

EAN: 5055387656604, Colour: White

<b>Display/image</b>	
Display technology	DLP™
Resolution	1080p Full HD (1920x1080)
Brightness	3,500 lumens
Contrast ratio	32,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - vertical	+/-40°
Horizontal scan rate	15 ~ 91Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	80%
Screen size	26.21" ~ 303.3" diagonal
<b>Lamp info</b>	
Light source type	Lamp
Lamp watts	260
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
<b>Optical</b>	
Throw ratio	1.4:1 ~ 2.24:1
Projection distance	51.18" - 370.08"
Zoom	1.6
Zoom type	Manual
Focal length (mm)	20.91mm~32.62mm/0.823"~1.284"
Lens shift	Vertical +17%
Native offset	99%
Lens shift	Yes - {{downloads_link}}
<b>Connectivity</b>	
Connections	<b>Inputs</b> 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support <b>Outputs</b> 1 x Audio 3.5mm, 1 x USB-A power 1A <b>Control</b> 1 x 3D sync, 1 x 12V trigger, 1 x mini USB service
<b>General</b>	
Noise level (typical)	29dB
Noise level (max)	31dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	Backlit home remote
Speaker count	1
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Input lag	16.00ms
Optional wireless models	WHID200
<b>Power</b>	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	249W
Power consumption (max)	309W
<b>Weight and dimensions</b>	
Dimensions (W x D x H)	12.4" x 8.82" x 4.49"
Gross weight	8.2 lbs
Net weight	6.19 lbs

