

CinemaX P1

CinemaX 4K UHD ultra short throw laser projector



- **Ultra short throw laser projector - 4K UHD resolution, HDR and HLG compatible**
- **Amazing colour - 87% DCI-P3, 3000 ANSI lumens**
- **Built-in soundbar with DolbyDigital 2.0**
- **Smart features - Apps, voice control, IFTTT**



Part of the CinemaX range, this stylish ultra short throw projector delivers an unforgettable 4K UHD digital cinema quality image in the comfort of your own home. Laser technology provides accurate, true to life colour reproduction with 87% of DCI-P3 coverage - perfect for recreating the big-screen experience at home.

Packed with the latest technology and features, the CinemaX P1 boasts HDR and HLG compatibility, sophisticated PureMotion frame-interpolation processing which eliminates motion blurring or image judder, voice control, streaming apps and a built-in media player.

Specifications

Display/imagen	
Tecnología de visualización	DLP™
Resolución	UHD (3840x2160)
Brillo	3,000 lumens
Ratio de contraste	1,500,000:1
Relación de aspecto nativo	16:9
Ratio de aspecto - compatible	4:3
Frecuencia de muestreo horizontal	31 ~ 135Khz
Frecuencia de muestreo vertical	24 ~ 120Hz
Uniformidad	90%
Tamaño de pantalla	85" ~ 120" diagonal
Info Lámpara	
Fuente de luz	Laser
Vida del LÁSER	30,000horas
Óptica	
Distancia de tiro	0.25:1
Distancia de proyección (m)	18.5" - 25.98"
Distancia focal (mm)	525mm/20.669"
Offset nativo	124%
Conectividad	
Conexiones	Entradas 2 x HDMI 2.0, 1 x USB-A lector Salidas 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm, 1 x HDMI 1.4a / 3D Control 1 x USB-A servicio, 1 x RJ45
General	
Nivel sonoro (tipico)	26dB
Nivel sonoro (max)	28dB
Compatibilidad PC	UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Compatibilidad 2D	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)
Compatibilidad 3D	Frame-pack: 1080p24, 720p50 / 60
3D	Full 3D
Seguridad	Kensington Lock, Interfaz protegida por contraseña
idiomas OSD / display	11 idiomas: Inglés, Francés, Alemán, Italiano, Japonés, Portugués, Ruso, Chino (simplificado), Español, Chino (tradicional)
Condiciones de funcionamiento	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Control remoto	Si
Altavoces	2
Watios por altavoz	20W
Contenido de la caja	CinemaX P1, AC power cable, Rechargeable Remote Control, Addendum, Quick Start Card Basic user manual
Input lag	70.00ms
Corriente	
Fuente de alimentación	100 ~ 240V, 50 ~ 60Hz
Consumo energético (standby)	0.5W
Consumo energético (mín.)	255W
Consumo energético (máx.)	410W
Peso y dimensiones	
Dimensiones (W x D x H)	22.68" x 15.08" x 5.12"
Gross weight	29.76 lbs
Net weight	24.25 lbs

