

ZH340ST

Ultra-compact Short Throw Full HD Laser Projector









- Bright Full HD 1080p DuraCore laser projector -3200 lumens and IP6X certified
- Ultra compact and short throw lens for easy installation - 360-degree and portrait projection
- Reduced power consumption for a long life span -DuraCore laser technology delivers 30,000 hours maintenance free laser light source
- External power supply More reliability, portability and energy efficiency



The ZH340ST is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, this 3200-lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹

An added benefit, the ZH340ST features an external power supply offering more reliability, portability and energy efficiency.

Specifications

The following specifications are preliminary and subject to change without notice

Display/image

DI P™ Display technology

Resolution 1080p Full HD (1920x1080)

Brightness 3,200 lumens Contrast ratio 300,000:1 1.800.000:1 Contrast ratio - dynamic Native aspect ratio 16:9 Aspect ratio - compatible 4:3,16:9,16:10 Keystone correction -+/-30°

horizontal

+/-30° Keystone correction - vertical Has vertical auto keystone Yes correction Displayable colours (millions) 1073.4 15 ~ 140Khz Horizontal scan rate Vertical scan rate 24 ~ 120Hz

Uniformity 75%

0.76m ~ 7.62m (30" ~ 300") diagonal Screen size

Lamp info Light source type Laser LASER life 30,000 hours

Optical Throw ratio

Projection distance 0.3m - 3.3m / 11.81" - 129.92"

Fixed Zoom type Focal length 7.51 Native offset 116%

Connectivity Connections

OSD / display languages

Inputs 2 x HDMI 2.0

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232

General Noise level (typical) 32dB Noise level (max) 34dB

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz 2D compatibility

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

3D compatibility Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D)

720p50 / 60

3D Full 3D

Security bar, Kensington Lock, Password protected interface Security

IP rating 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

24/7 operation Yes 360° operation Yes

 $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$, Max. Humidity 80%, Max. Altitude 2,500m Operating conditions

Remote control Card style Speaker count Watts per speaker 15W In the box AC power cord

Remote Control w/ CR2025 Battery

Input lag 8.60ms

Optional wireless models QuickCast Pro 4K KIT Power 100V ~ 240V, 50-60Hz Power supply

<0.5W Power consumption (standby) Power consumption (min) 98W 139W Power consumption (max)

Weight and dimensions

Dimensions (W x D x H) 10.79" x 8.5" x 4.49" Gross weight 9.26 lbs Net weight 6.61 lbs UPC 796435 44 695 6



