

# SH360

## Bright Home Entertainment Projector



### Features

- Luminous projection with 3,600 lumens and 22,000:1 contrast ratio
- HDMI, VGA and composite connectivity
- Accepts 720p and 1080p High Definition Signals
- Up to 15,000-hour lamp life
- Vertical keystone for easy positioning
- Integrated 10-watt speaker



Supersize video experiences with the 3,600 lumens Optoma SH360. The compact and lightweight chassis makes it easy to transport and setup for a quick huge screen movie night anywhere – up to 300 inches.

Robust input options, including HDMI, VGA and composite enable connectivity to a wide range of digital and analog devices. A 15,000-hour lamp life enables many years of use with minimal maintenance.



# SH360



## TECHNICAL SPECIFICATIONS

Aspect Ratio	4:3
Audio	10W speaker
Brightness	3,600 ANSI lumens
Compatible Aspect Ratio	4:3 (native), 16:9 and auto compatible
Connections	1 x HDMI v1.4a, 1 x VGA, 1 x composite, 1 x audio-in, 1 x USB-A (5v / 1.0 amp), 1 x VGA, 1 x audio, 1 x RS232
Contrast Ratio	22,000:1
Control Unit	RS-232C
Display Technology	Texas Instruments 0.55" SVGA DMD
Displayable Colors	1.07 billion
Keystone Correction	± 40° Vertical
Light Source Type	203W
Light Source Life	15,000/12,000/10,000/6,000 (Eco+/Dynamic/Eco/Bright)
Lens Shift	None
Maximum Resolution	1080p (1920 x 1080)
Native Resolution	SVGA (800 x 600)
Noise Level	27dB
Offset	115%±5%
Operating Temperature	41-104°F (5-40°C)
Power Consumption	230W (Bright) / 190W (Eco)
Power Supply	AC input 100-240V, 50-60 Hz, auto-switching

Projection Distance	3.9' - 46.9' (without zoom)
Projection Lens	F=2.5 - 3.39, F=17.63 - 31.36mm Manual Focus
Projection Screen Size	27.7" - 304.4"
Remote Control	IR remote control
Throw Ratio	1.94 - 2.15 ±5%

## COMPATIBILITY SPECIFICATIONS

3D Compatibility	Side-by-Side: 1080i50 / 60, 720p50 / 60, Frame-pack: 1080p24, 720p50 / 60, Over-Under: 1080p24, 720p50 / 60
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA resized, VESA, PC and Mac compatible
Horizontal Scan Rate	15.375 - 91.146 KHz
RoHS	Compliant
Vertical Scan Rate	50-85 Hz (120Hz for 3D feature projector)
Video Compatibility	480p, 720p, 1080p, SDTV, HDTV

## PHYSICAL SPECIFICATIONS

Dimensions (W x H x D)	12.4" x 3.9" x 9.6"
Security	Security bar, Kensington lock, password protection, keypad lock
Weight	6.7 lbs.

## Other

What's in the Box?	SH360, AC power cable, remote control, batteries, quick start user manual
Accessories Part Numbers	4K UHD Casting and Mirror Dongle: UHDCast Pro, Carrying case: BK-4028, Lamp (replacement): BL-FU200D, Remote (replacement): BR-3079N, Universal ceiling mount: BM-5001U, Universal Ceiling mount: OCM815W, Universal Ceiling mount: OCM818W-RU
UPC	796435 81 384 0
Warranty Info	1 Year limited parts and labor warranty on the projector, 90 days lamp warranty

\*Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

† 3D content can be viewed with DLP® Link active shutter glasses when projector is used with a compatible 3D player. Please visit Optoma.com for more information.

Optoma.com

Copyright © 2020 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change.  
Published on 12/14/20